


AMENDMENTS TO THE CLAIMS:


Please amend the claims to read as follows:

1. (Currently Amended) A fuel cell ~~An electrode structure for polymer electrolyte fuel cells~~, comprising a pair of electrode catalyst layers, each containing a catalyst supported by carbon particles and ion-conductive binder, and a polymer electrolyte membrane placed between the electrode catalyst layers,

wherein the polymer electrolyte membrane is formed from a sulfonated polyarylene consisting of 0.5 to 100% by mol of a first repeating unit represented by the general formula (1) and 0 to 99.5% by mol of a second repeating unit represented by the general formula (2):




(wherein, A is a divalent organic group; and a benzene ring includes its derivative),



(wherein, -W- is a divalent electron attracting group; -T- is a divalent organic group; and R¹ to R⁸ are a hydrogen atom or fluorine atom, an alkyl group, fluorine-substituted alkyl group, allyl group, aryl group or cyano group, and may be the same or different).

3. (Currently amended) A fuel cell ~~The electrode structure for polymer electrolyte fuel cells~~ according to claim 1, wherein said polymer electrolyte membrane is composed of a sulfonated polyarylene represented by the general formula (3):




5. (Original) A polymer electrolyte fuel cell comprising an electrode structure for polymer electrolyte fuel cells, which comprises a pair of electrode catalyst layers, each containing a catalyst supported by carbon particles, and a polymer electrolyte membrane placed between these electrode catalyst layers, the polymer electrolyte membrane being formed by a sulfonated polyarylene as a copolymer consisting of 0.5 to 100% by mol of a first repeating unit represented by the general formula (1) and 0 to

99.5% by mol of a second repeating unit represented by the general formula (2):




(wherein, A is a divalent organic group; and a benzene ring includes its derivative),




(wherein, -W- is a divalent electron attracting group; -T- is a divalent organic group; and R¹ to R⁸ are a hydrogen atom or fluorine atom, an alkyl group, fluorine-substituted alkyl group, allyl group, aryl group or cyano group, and may be the same or different), wherein a fuel gas is supplied to one of the electrode catalyst layers and an oxidizing gas is supplied to the other electrode catalyst layer.

6. (Currently Amended) An electrical device which ~~uses~~ comprises a polymer electrolyte fuel cell comprising an electrode structure for polymer electrolyte fuel cells, which comprises a pair of electrode catalyst layers, each containing a catalyst supported by carbon particles, and a polymer electrolyte membrane placed between these electrode catalyst layers, the polymer electrolyte membrane being formed by of a sulfonated polyarylene as a copolymer consisting of 0.5 to 100% by mol of a first repeating unit represented by the general formula (1) and 0 to 99.5% by mol of a second repeating unit represented by the general formula (2):




(wherein, A is a divalent organic group; and a benzene ring includes its derivative),




(wherein, -W- is a divalent electron attracting group; -T- is a divalent organic group; and R¹ to R⁸ are a hydrogen atom or fluorine atom, an alkyl group, fluorine-substituted alkyl group, allyl group, aryl group or cyano group, and may be the same or different), and a fuel gas is supplied to one of the electrode catalyst layers and an oxidizing gas is supplied to the other electrode catalyst layer.

7. (Currently Amended) A transportation device which uses comprises a polymer electrolyte fuel cell comprising an electrode structure for polymer electrolyte fuel cells, which comprises a pair of electrode catalyst layers, each containing a catalyst supported by carbon particles, and a polymer electrolyte membrane placed between these electrode catalyst layers, the polymer electrolyte membrane being formed by a sulfonated polyarylene as a copolymer composed of 0.5 to 100% by mol of a first repeating unit represented by the general formula (1) and 0 to 99.5% by mol of a second repeating unit represented by the general formula (2):



(wherein, A is a divalent organic group; and a benzene ring includes its derivative),



(wherein, -W- is a divalent electron attracting group; -T- is a divalent organic group; and R¹ to R⁸ are a hydrogen atom or fluorine atom, an alkyl group, fluorine-substituted alkyl group, allyl group, aryl group or cyano group, and may be the same or different), and a fuel gas is supplied to one of the electrode catalyst layers and an oxidizing gas is supplied to the other electrode catalyst layer.

8. (New) The fuel cell of claim 1, wherein R¹ to R⁸ are an aryl group or a cyano group, and may be the same or different.
9. (New) The polymer electrolyte fuel cell of claim 5, wherein R¹ to R⁸ are an aryl group or a cyano group, and may be the same or different.
10. (New) The electrical device of claim 6, wherein R¹ to R⁸ are an aryl group or a cyano group, and may be the same or different.

11. (New) The transportation device of claim 7, wherein R¹ to R⁸ are an aryl group or a cyano group, and may be the same or different.